Serial No.: 10/612,931

AMENDMENTS TO THE CLAIMS:

1. (Currently Amended) A vehicle air conditioning system comprising:

an air conditioning unit for generating air-conditioned air, which is provided with a ventilation opening and a defroster opening;

a ventilation duct connected to the air conditioning unit at the ventilation opening, which conducts the air-conditioned air to a ventilation outlet;

a defroster duct connected to the air conditioning unit at the defroster opening, which conducts the air-conditioned air to a defroster outlet; and

an additional duct branching off from the defroster duct, which conducts the airconditioned air from the defroster duct to an upper ventilation outlet which is provided on an
upper surface of an instrument panel to blow the air-conditioned air toward the upper rear of a
passenger compartment[[.]], only when any one of a ventilation mode, a bi-level mode, and a
foot mode is selected.

2. (Original) The vehicle air conditioning system according to claim 1, further comprising:

a switching damper for selectively conducting the air-conditioned air from the defroster duct to either the defroster outlet or the additional outlet.

3. (Original) The vehicle air conditioning system according to claim 2, further comprising:

an open/close damper for opening and closing passage of the air-conditioned air of the additional duct.

Serial No.: 10/612,931

Claim 4 (Cancelled)

Claim 5 (Withdrawn)

6. (Original) The vehicle air conditioning system according to claim 1, further comprising:

a ventilation damper for opening and closing the ventilation opening of the air conditioning unit, wherein the ventilation damper is controlled to open and close the ventilation opening in dependence on a selected air distribution mode, and wherein

the defroster opening is kept open irrespective of the selected air distribution mode.

7. (Currently Amended) A vehicle air conditioning system comprising: an air conditioning unit for generating air-conditioned air;

first and second ducts connected to the air conditioning unit, the first duct conducting the air-conditioned air to a ventilation outlet, the second duct conducting the air-conditioned air to a defroster outlet; [[and]]

a third duct branching off from the second duct, which conducts the air-conditioned air to one of an upper ventilation outlet provided on an upper surface of an instrument panel to blow the air-conditioned air toward the upper rear of a passenger compartment or a rear ventilation outlet provided near a vehicle rear [[seat.]] seat; and

a damper configured to selectively open the second duct or the third duct.

Serial No.: 10/612,931

8. (Currently Amended) A vehicle air conditioning system comprising: an air conditioning unit for generating air-conditioned air;

a first path for conducting the air-conditioned air from the air conditioning unit to a ventilation outlet;

a second path for conducting the air-conditioned air from the air conditioning unit to a defroster outlet to blow the air-conditioned air toward a windshield; and

a third path branching off from the second path for conducting the air-conditioned air to an additional outlet other than the ventilation outlet and the defroster outlet. when blowing the air-conditioned air from the defroster outlet is stopped.